

The better way to build™



# Installation Manual

## EXTERIOR WALL SIPs



**Thermapan**  
Structural  
Insulated  
Panels

## **EXTERIOR WALL SIPs Installation Manual**

### **Table of Contents**

#### **Topics**

|                                |   |
|--------------------------------|---|
| General Requirements . . . . . | 3 |
| Materials . . . . .            | 3 |
| Electrical Wiring . . . . .    | 3 |
| Interior Finish . . . . .      | 4 |
| Exterior Cladding . . . . .    | 4 |

#### **Details**

|  |        |
|--|--------|
| Air Barrier Details for Air Barrier Sealants . . . . .   | AB-1   |
| Air Barrier Details for Sealing SIP Connections . . . . .  | AB-2   |
| Vapour Barrier Details for Vapour Sealing SIP Connections . . .                                    | VB-1   |
| Foam Core (SIP) Spline Detail . . . . .  | W-1    |
| Wood Stud Spline Joint Detail . . . . .  | W-2    |
| Typical Wall Section . . . . .   | W-3    |
| Floor-to-Wall Connection Detail . . . . .  | W-4    |
| Sill Plate Detail . . . . .  | W-5    |
| Wall Butt Corner Connection Detail . . . . .   | W-6    |
| Window Cut-Out (Non-Load Bearing Wall) . . . . .   | W-7    |
| Panel Lintel/Header Details & Bearing Conditions 1-4 . . . . .                                     | W-8    |
| Lintel Detail . . . . .  | W-9    |
| Point Load Detail . . . . .  | W-10   |
| Knee Wall Detail . . . . .   | W-11   |
| Door & Window Rough Openings . . . . .   | W-12   |
| Wood Ledger Attached to SIP Wall Panel . . . . .   | W-13   |
| Vertical Electrical Chase . . . . .  | W-14   |
| Exterior Wall Cladding - Brick & Stucco . . . . .  | W-15   |
| Exterior Wall Cladding - Siding . . . . .  | W-16   |
| 60 Min. Partywall Single Wall STC Rating 50 . . . . .  | PW-1   |
| Partywall Electrical Detail (60 Min. Wall Rated Assembly<br>(Single Wall) STC Rating 50) . . . . . | PW-2   |
| 60 Min. Partywall Double Wall STC Rating 50 . . . . .  | PW-3   |
| Partywall Electrical Detail (60 Min. Double Wall) . . . . .  | PW-4   |
| Vertical Panel Connections Spline & Corner (Timberframe) . .                                       | W-TF-1 |
| Horizontal Connections at Beams (Timberframe) . . . . .  | W-TF-2 |
| Foundation Details Deck Options (Timberframe) . . . . .  | W-TF-3 |

Appendix A: Allowable Header Loads – Panel Lintel/Headers

## **EXTERIOR WALL SIPs Installation Manual**

### **1. General Requirements**

#### **1.1 Scope**

The basic design and construction requirements for the Thermapan Structural Insulated Panel (SIP) wall system is set forth in this specification. Criteria for materials, environmental control, design loads, and structural design are included. Where requirements are based on internationally recognized standards and specifications, these standards and specifications are referenced without elaboration.

**Installers shall reference engineering design package for fastening arrangements.**

### **2. Materials**

- 2.1** The Thermapan Wall SIP is composed of an expanded polystyrene (EPS) foam core laminated between two layers of oriented strand board (OSB) with a structural adhesive. (See Detail W-1)
- 2.2** Framing Lumber shall be DOC PS 20 or NLGA No.2 or better.
- 2.3** Wire nails, ring nails, spikes and staples shall conform to CSA B111 or ANSI/ASME B11.1.
- 2.4** Wood screws shall conform to ANSI/ASME B18.6.1..
- 2.5** SIP screws shall conform to ICC-AC233.
- 2.6** Caulking Compounds shall conform to CAN/CGSB 19.13 or ASTM C 920.
- 2.7** Polyethylene Sheeting shall conform to CAN/CGSB-37.2, CAN/CGSB-37.16, or ASTM D 4397.
- 2.8** Low expansion foam seal shall conform to AAMA 812-04.
- 2.9** Structural adhesive shall conform to CAN/CGSB 71GP26, APA AFG-01 or ASTM D3498.

### **3. Electrical Wiring**

- 3.1** All wire chases to be vertically cut into the wall SIP at a minimum depth of 2". See Detail W-14.

#### **4. Interior Finish**

- 4.1** The interior of the wall SIP can be finished with any of the common required building code materials. It is recommended that the SIP joints and connections be sealed as per Details AB-1, AB-2 and VB-1.

#### **5. Exterior Cladding**


- 5.1** A weather barrier is to be installed over the exterior OSB of the SIP and under the cladding and/or furring. Refer to Details W-15 and W-16 and your local building code for compliant weather barrier materials.

# AIR BARRIER



## RECOMMENDED DETAILS FOR AIR BARRIER SEALANTS

All sealants, FOAM (A) or CAULKING (B), should be applied onto the SIP in a continuous rectangular pattern along the outer most edge of the area to be sealed.

(A) A low expansion EXPANDABLE FOAM SEALANT should conform to the AAMA 812-04 standard. Apply a 1/2 inch or a 12.5 mm diameter of a *continuous* bead of expandable foam sealant onto the SIP:



(B) A CAULKING SEALANT should conform to ASTM C920-02 and/or CAN/CGSB 19.13-M. Apply a 3/8 inch or a 10 mm diameter *continuous* bead of caulking onto the lumber spline:




www.thermapan.com  
1-877-443-WALL (9255)

|   |          |          |  |
|---|----------|----------|--|
| TITLE   |          | PROJECT  |  |
| AIR BARRIER DETAILS<br>FOR AIR BARRIER SEALANTS |          |          |  |
| REFERENCE                                       | SCALE    |          |  |
|   | N.T.S.   |          |  |
| DATE  | REVISION | DWG. No. |  |
| NOVEMBER 2010                                   | 1        | AB-1     |  |


# AIR BARRIER

## RECOMMENDED DETAILS FOR SEALING SIP CONNECTIONS


(1) Foam to Foam: Use a low expansion foam sealant.



(2) Foam to Wood: Use a low expansion foam sealant.



(3) Wood to Wood: Use caulking and a low expansion foam sealant.



www.thermapan.com  
1-877-443-WALL (9255)

|   |          |          |  |
|---|----------|----------|--|
| TITLE   |          | PROJECT  |  |
| AIR BARRIER DETAILS FOR SEALING SIP CONNECTIONS |          |          |  |
| REFERENCE                                       | SCALE    |          |  |
|   | N.T.S.   |          |  |
| DATE  | REVISION | DWG. No. |  |
| MAY 2009  |          | AB-2     |  |


# VAPOUR BARRIER

## RECOMMENDED DETAILS FOR VAPOUR SEALING SIP CONNECTIONS


The function of a vapour barrier is to control the entry of water vapour into the building assembly. Vapour barriers should not be confused with an air barrier.

All SIP seams and connections must be VAPOUR SEALED from the INTERIOR.


These are recommended vapour barrier methods:




CONTINUOUS 6 MIL POLY  
**RECOMMENDED**




6 MIL POLY STRIPS & CAULKING



CAULKING




SIP TAPE




www.thermapan.com  
1-877-443-WALL (9255)

|   |          |          |  |
|---|----------|----------|--|
| TITLE   |          | PROJECT  |  |
| VAPOUR BARRIER DETAILS FOR VAPOUR SEALING SIP CONNECTIONS |          |          |  |
| REFERENCE   | SCALE    |          |  |
|   | N.T.S.   |          |  |
| DATE  | REVISION | DWG. No. |  |
| NOVEMBER 2010   | 1        | VB-1     |  |


**ISOMETRIC  
VIEW**



**TOP  
VIEW**




**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.




www.thermapan.com  
1-877-443-WALL (9255)

|               |          |                                  |        |
|---------------|----------|----------------------------------|--------|
| TITLE         |          | FOAM CORE (SIP)<br>SPLINE DETAIL |        |
| REFERENCE     | SCALE    |                                  | N.T.S. |
| DATE          | REVISION | DWG. No.                         |        |
| FEBRUARY 2012 | 5        | W-1                              |        |


**ISOMETRIC  
VIEW**



**TOP  
VIEW**




**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.




www.thermapan.com  
1-877-443-WALL (9255)

|               |  |          |                                  |  |  |
|---------------|--|----------|----------------------------------|--|--|
| TITLE         |  |          | WOOD STUD SPLINE<br>JOINT DETAIL |  |  |
| REFERENCE     |  | SCALE    |                                  |  |  |
|               |  | N.T.S.   |                                  |  |  |
| DATE          |  | REVISION | DWG. No.                         |  |  |
| FEBRUARY 2012 |  | 5        | W-2                              |  |  |




**SECTION**


**DETAIL A**



**DETAIL B**





**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.




www.thermapan.com  
1-877-443-WALL (9255)

|                      |  |          |  |
|----------------------|--|----------|--|
| TITLE                |  | PROJECT  |  |
| REFERENCE            |  | SCALE    |  |
| DATE                 |  | REVISION |  |
| NOVEMBER 2012        |  | 5        |  |
| TYPICAL WALL SECTION |  | N.T.S.   |  |
|                      |  | DWG. No. |  |
|                      |  | W-3      |  |


# PLATFORM FRAMING



# SUSPENDED FLOOR DETAIL




**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.



www.thermapan.com  
1-877-443-WALL (9255)

|                                    |          |          |  |
|------------------------------------|----------|----------|--|
| TITLE                              |          | PROJECT  |  |
| FLOOR-TO-WALL<br>CONNECTION DETAIL |          |          |  |
| REFERENCE                          | SCALE    |          |  |
|                                    | N.T.S.   |          |  |
| DATE                               | REVISION | DWG. No. |  |
| FEBRUARY 2012                      | 4        | W-4      |  |




**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.




**Thermapan**  
Structural  
Insulated  
Panels

www.thermapan.com  
1-877-443-WALL (9255)

|                   |          |          |  |
|-------------------|----------|----------|--|
| TITLE             |          | PROJECT  |  |
| SILL PLATE DETAIL |          |          |  |
| REFERENCE         | SCALE    |          |  |
|                   | N.T.S.   |          |  |
| DATE              | REVISION | DWG. No. |  |
| FEBRUARY 2012     | 3        | W-5      |  |




**CORNER DETAIL**  
(FOR BRICK VENEER OR SIDING)



**CORNER DETAIL**  
(FOR STUCCO)


**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.



www.thermapan.com  
1-877-443-WALL (9255)

|                                    |          |          |  |
|------------------------------------|----------|----------|--|
| TITLE                              |          | PROJECT  |  |
| WALL BUTT CORNER CONNECTION DETAIL |          |          |  |
| REFERENCE                          | SCALE    |          |  |
|                                    | N.T.S.   |          |  |
| DATE                               | REVISION | DWG. No. |  |
| FEBRUARY 2012                      | 3        | W-6      |  |

- ① NON-LOAD BEARING WALL:  
MAX. UNFACTORED LIVE LOAD = 160 lb./ft. (2.4 kN/m)  
MAX. UNFACTORED DEAD LOAD = 50 lb./ft. (0.75 kN/m)





**CONDITIONS**

- ① NON-LOAD BEARING WALL
- ② MINIMUM LINTEL HEIGHT OF 12" (305 mm)
- ③ MAXIMUM OPENING WIDTH OF 48" (1220 mm)

FOR ROUGH OPENINGS A DEPTH OF 1-1/2" (38 mm) OF FOAM IS REMOVED FROM THE PERIMETER OF THE OPENING. THE ROUTED SPACE IS THEN FILLED WITH MATERIAL CONSISTENT WITH THE THICKNESS OF THE PANEL CORE.

THESE ARE SECURED IN PLACE WITH NAILS OR SCREWS @ 8" (203 mm) O/C MAX., TO CREATE THE ROUGH OPENING.



www.thermapan.com  
1-877-443-WALL (9255)


|   |          |          |  |
|---|----------|----------|--|
| TITLE   |          | PROJECT  |  |
| <b>WINDOW CUT-OUT<br/>(NON-LOAD BEARING WALL)</b> |          |          |  |
| REFERENCE   | SCALE    |          |  |
|   | N.T.S.   |          |  |
| DATE  | REVISION | DWG. No. |  |
| FEBRUARY 2012                                     | 2        | W-7      |  |

## DETAIL 1

### CONDITION 1:

- (1) MAX 9'-1" WALL HEIGHT
- (2) MAX 5,000 LBS. (22.3 kN) FACTORED REACTION
- (3) CONFIRM JACK POST REACTIONS
- (4) SINGLE JACK STUD

NOTE: REFER TO APPENDIX A OR DESIGN HANDBOOK FOR ALLOWABLE HEADER LOADS.




## DETAIL 2

### CONDITION 2:

- (1)  $9'-1" \leq X \leq 12'$  (WALL HEIGHT)
- (2) MAX 5,000 LBS. (22.3 kN) FACTORED REACTION
- (3) CONFIRM JACK POST REACTIONS
- (4) SINGLE JACK AND KING STUD

NOTE: OSB TO BE ADDED TO BOTH SIDES OF STUDS WHEN ONLY 1-1/2" FOAM RECESS IS PROVIDED IN WALL PANEL. REFER TO APPENDIX A OR DESIGN HANDBOOK FOR ALLOWABLE HEADER LOADS.



## DETAIL 3



### INSTALLING STUDS:

1. REMOVE OSB ONE SIDE
2. REMOVE FOAM
3. INSTALL STUDS
4. REPLACE OSB

### CONDITION 3:

- (1)  $X \geq 12'$  (WALL HEIGHT)
- (2) MAX 5000 LBS. (22.3 kN) FACTORED REACTION
- (3) CONFIRM JACK POST REACTIONS
- (4) SINGLE JACK AND DOUBLE KING STUDS

NOTE: REFER TO APPENDIX A OR DESIGN HANDBOOK FOR ALLOWABLE HEADER LOADS.



## DETAIL 4




### INSTALLING STUDS:

1. REMOVE OSB ONE SIDE
2. REMOVE FOAM
3. INSTALL STUDS
3. REPLACE OSB

### CONDITION 4:

- (1)  $X \geq 12'$  (WALL HEIGHT)
- (2) MAX 10,000 LBS. (44.6 kN) FACTORED REACTION
- (3) CONFIRM JACK POST REACTIONS
- (4) DOUBLE JACK AND DOUBLE KING STUDS

NOTE: REFER TO APPENDIX A OR DESIGN HANDBOOK FOR ALLOWABLE HEADER LOADS.



www.thermapan.com  
1-877-443-WALL (9255)

TITLE

## PANEL LINTEL/HEADER DETAILS & BEARING CONDITIONS 1 - 4

PROJECT

REFERENCE

SCALE

N.T.S.


DATE

SEPTEMBER 2011

REVISION

DWG. No.


W-8



**Thermapan**  
Structural  
Insulated  
Panels


www.thermapan.com  
1-877-443-WALL (9255)

|   |          |          |  |
|---|----------|----------|--|
| TITLE                                       |          | PROJECT  |  |
| <b>LINTEL DETAIL<br/>(HEADER BY OTHERS)</b> |          |          |  |
| REFERENCE                                   | SCALE    |          |  |
|   | N.T.S.   |          |  |
| DATE  | REVISION | DWG. No. |  |
| SEPTEMBER 2011                              | 4        | W-9      |  |



NOTE: INSTALL COLUMN AS PER LOCAL BUILDING CODE.


NOTE 2: REMOVE BOTTOM PLATE SECTION AND INSTALL COLUMN DIRECTLY ONTO FLOOR IF LOAD IS GREATER THAN BEARING RESISTANCE OF WOOD PLATE.




www.thermapan.com  
1-877-443-WALL (9255)

|                   |          |          |  |
|-------------------|----------|----------|--|
| TITLE             |          | PROJECT  |  |
| POINT LOAD DETAIL |          |          |  |
| REFERENCE         | SCALE    |          |  |
|                   | N.T.S.   |          |  |
| DATE              | REVISION | DWG. No. |  |
| FEBRUARY 2012     | 4        | W-10     |  |

KNEE WALL SET  
ONTO FLOOR FOR  
ATTIC OR RAISED  
ROOF SPACE  
ENCLOSURE



REFER TO WALL  
DETAILS W-2 OR W-3



**Thermapan**  
Structural  
Insulated  
Panels

www.thermapan.com  
1-877-443-WALL (9255)

TITLE

**KNEE WALL DETAIL**

PROJECT

REFERENCE

SCALE

**N.T.S.**

DATE



**MAY 2009**

REVISION

**1**

DWG. No.


**W-11**




FOR ROUGH OPENINGS A DEPTH OF 1 1/2 " OF FOAM IS REMOVED FROM THE PERIMETER OF THE OPENING. THE ROUTED SPACE IS THEN FILLED WITH A MATERIAL CONSISTENT WITH THE THICKNESS OF THE PANEL CORE.

THESE ARE SECURED IN PLACE WITH NAILS OR SCREWS @8" O/C MAX., TO CREATE THE ROUGH OPENING.

THE WINDOW OR DOOR IS THEN INSTALLED CONVENTIONALLY.




NOTE: REFER TO LINTEL DETAILS W-7.




www.thermapan.com  
1-877-443-WALL (9255)

|                                 |          |          |  |
|---------------------------------|----------|----------|--|
| TITLE                           |          | PROJECT  |  |
| DOOR & WINDOW<br>ROUGH OPENINGS |          |          |  |
| REFERENCE                       | SCALE    | N.T.S.   |  |
| DATE                            | REVISION | DWG. No. |  |
| FEBRUARY 2012                   | 3        | W-12     |  |





LEDGER CAN ALSO BE NAILED OR SCREWED (3.5" LONG) INTO LUMBER SPLINES (IF USED) AT 4' O/C



www.thermapan.com  
1-877-443-WALL (9255)


|   |          |          |  |
|---|----------|----------|--|
| TITLE   |          | PROJECT  |  |
| WOOD LEDGER ATTACHED TO SIP WALL PANEL <sup>®</sup> |          |          |  |
| REFERENCE   | SCALE    | NTS      |  |
| DATE  | REVISION | DWG. No. |  |
| FEBRUARY 2012                                       | 2        | W-13     |  |

ISOMETRIC



NOTES:


1. MAXIMUM OF TWO (2) VERTICAL CHASES PERMITTED FOR WALL PANELS 2'-6" (760mm) TO 4' (1220 mm) WIDE, MINIMUM 18"(457mm) APART.
2. MAXIMUM OF ONE (1) VERTICAL CHASE PERMITTED FOR WALL PANELS LESS THAN 2'-6" WIDE (760mm) .



www.thermapan.com  
1-877-443-WALL (9255)

|  |          |          |  |
|--|----------|----------|--|
| TITLE                                  |          | PROJECT  |  |
| VERTICAL ELECTRICAL CHASE <sup>®</sup> |          |          |  |
| REFERENCE                              | SCALE    |          |  |
| DATE                                   | REVISION | DWG. No. |  |
| JANUARY 2012                           | 1        | W-14     |  |

## MASONRY VENEER



2" RING NAILS OR  
#8 (MINIMUM) SCREWS  
WITH FULL PENETRATION INTO OSB

MASONRY TIES  
INSTALLED @  
16" O/C VERTICALLY &  
24" O/C HORIZONTALLY  
(MAXIMUM)  
AS PER BUILDING CODE



BRICK  
VENEER

WEATHER  
BARRIER

OSB

EPS


## STUCCO



www.thermapan.com  
1-877-443-WALL (9255)

|  |          |          |  |
|--|----------|----------|--|
| TITLE                                    |          | PROJECT  |  |
| EXTERIOR WALL CLADDING<br>BRICK & STUCCO |          |          |  |
| REFERENCE                                | SCALE    |          |  |
|  | N.T.S.   |          |  |
| DATE                                     | REVISION | DWG. No. |  |
| FEBRUARY 2011                            | 1        | W-15     |  |


## VINYL SIDING



## FIBRE CEMENT SIDING

FOR FIBRE CEMENT LAP SIDING REFER TO MANUFACTURER'S RECOMMENDED FASTENING METHODS.

## WOOD SIDING



### FURRING REQUIREMENTS

| FURRING SPACING | FASTENER SPACING (MIN 1-1/2" SCREWS) | FASTENER SPACING (MIN 1-1/4" NAILS) |
|-----------------|--------------------------------------|-------------------------------------|
| 16" O/C         | 10" O/C                              | 8" O/C                              |
| 24" O/C         | 8" O/C                               | 8" O/C                              |

NOTE: ALL NAILS TO BE RING (ANNULARLY THREADED). FURRING TO BE AS RECOMMENDED BY SIDING MANUFACTURER.



www.thermapan.com  
1-877-443-WALL (9255)

|                                   |                 |          |  |
|-----------------------------------|-----------------|----------|--|
| TITLE                             |                 | PROJECT  |  |
| EXTERIOR WALL CLADDING:<br>SIDING |                 |          |  |
| REFERENCE                         | SCALE<br>N.T.S. |          |  |
| DATE                              | REVISION        | DWG. No. |  |
| FEBRUARY 2011                     | 1               | W-16     |  |

TRUSSES INSTALLED AS PER LOCAL BUILDING CODE

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
SONOSECUR ACOUSTICAL PANEL  
(one side only)  
1/2" RESILIENT CHANNEL RC-1  
6 1/2" STRUCTURAL FOAM  
CORE PANEL

CONT. FIRE RATED  
CAULKING TYP.

INSTALL AS PER LOCAL  
BUILDING CODE OR JOIST  
SUPPLIER SPEC.

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
SONOSECUR ACOUSTICAL PANEL  
(one side only)  
1/2" RESILIENT CHANNEL RC-1  
6 1/2" STRUCTURAL FOAM  
CORE PANEL

CONT. FIRE RATED CAULKING TYP.

INSTALL AS PER LOCAL  
BUILDING CODE OR JOIST  
SUPPLIER SPEC.

POURED CONCRETE OR  
BLOCK FOUNDATION  
WALL

PARTYWALL  
\* UL / ULC LABELLED GYPSUM SHEATHING

STRUCTURAL CAPACITY FOR WALL  
NOT TO EXCEED 32.4 kn/m  
(2217 LBS. PER LINEAR FOOT)  
FOR OTHER REQUIREMENTS,  
INCLUDING STRUCTURAL LOAD,  
REFER TO MANUFACTURER'S  
INSTRUCTIONS.


INSTALL TOP PLATE AND CAP  
SECURED TO STUDS WITH 95 mm  
SPIRAL NAILS

50 mm RING NAILS  
@ 250 mm O/C (TYP.)

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
1/2" RESILIENT CHANNEL

DOUBLE STUD SPLINE  
SECURED TO PLATE WITH  
83 mm SPIRAL NAILS


NOTE: TESTED IN CONFORMANCE WITH  
CAN/ULC-S101-M, "FIRE ENDURANCE  
TESTS OF BUILDING CONSTRUCTION  
AND MATERIALS"



www.thermapan.com  
1-877-443-WALL (9255)

|                |  |          |  |  |  |
|----------------|--|----------|--|--|--|
| TITLE          |  |          | 60 MIN. PARTYWALL<br>SINGLE WALL STC RATING 50 |  |  |
| REFERENCE      |  | SCALE    |  |  |  |
|                |  | N.T.S.   |  |  |  |
| DATE           |  | REVISION | DWG. No.                                       |  |  |
| SEPTEMBER 2011 |  | 7        | W-PW-1   |  |  |

NOTE: TESTED IN CONFORMANCE WITH CAN/ULC-S101-M, "FIRE ENDURANCE TESTS OF BUILDING CONSTRUCTION AND MATERIALS"



ASSEMBLY OF RESILIENT CHANNEL (5)

THE RESILIENT CHANNELS ARE ORIENTED VERTICALLY AT 16" (400 mm) OC AND SECURED WITH 1" (25 mm) TYPE W GYPSUM BOARD SCREWS AT 16" (400 mm) OC TO THE STRUCTURAL INSULATED PANEL (SIP)

ASSEMBLY OF SONOSECUR ACOUSTIC PANEL (4)

TACK THE SONOSECUR ACOUSTIC PANEL WITH 1" (25 mm) LONG TYPE W GYPSUM BOARD SCREWS TO HOLD IN PLACE. THE SONOSECUR ACOUSTIC PANEL IS ASSEMBLED ON ONE SIDE ONLY.


ASSEMBLY OF FIRST LAYER 5/8" TYPE C GYPSUM (6)

INSTALL THE FIRST GYPSUM LAYER (6) VERTICALLY ONTO RESILIENT CHANNELS WITH 1" (25 mm) TYPE W GYPSUM SCREWS SPACED 16" (400 mm) OC.

ASSEMBLY OF SECOND LAYER 5/8" TYPE C GYPSUM (7)

THE JOINTS OF THE SECOND LAYER SHOULD BE OFFSET AND STAGGERED FROM FIRST LAYER. THE SECOND LAYER SHOULD HAVE 1.75" (44 mm) SCREWS AT 12" (304 mm) OC . THE FIRST LAYER OF GYPSUM DOES NOT HAVE TO BE TAPED. ONLY THE SECOND LAYER HAS TO BE FINISHED. JOINTS SHOULD BE COVERED WITH COMPOUND, COVERED WITH JOINT TAPE AND COVERED WITH AN ADDITIONAL TWO COATS OF JOINT COMPOUND. SCREW HEADS COVERED WITH JOINT COMPOUND.

UL GYPSUM BOARD FIRECODE "C"



www.thermapan.com  
1-877-443-WALL (9255)

|   |          |          |
|---|----------|----------|
| TITLE   |          |          |
| PARTYWALL ELECTRICAL DETAIL<br>(60 MINUTE WALL RATED ASSEMBLY<br>(SINGLE WALL) STC RATING 50) |          |          |
| REFERENCE   | SCALE    |          |
| 8015  | N.T.S.   |          |
| DATE  | REVISION | DWG. No. |
| SEPTEMBER 2011  | 7        | W-PW-2   |

TRUSSES INSTALLED AS PER BUILDING CODE

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
SONOSECUR ACOUSTICAL PANEL  
(one side only)  
1/2" RESILIENT CHANNEL RC-1  
4 1/2" STRUCTURAL FOAM  
CORE PANEL

1" AIR SPACE

CONTINUOUS FIRE RATED CAULKING

INSTALL AS PER LOCAL BUILDING CODE OR JOIST SUPPLIER SPEC.

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
SONOSECUR ACOUSTICAL PANEL  
(one side only)  
1/2" RESILIENT CHANNEL RC-1  
4 1/2" STRUCTURAL FOAM  
CORE PANEL

1" AIR SPACE

CONTINUOUS FIRE RATED CAULKING

INSTALL AS PER LOCAL BUILDING CODE OR JOIST SUPPLIER SPEC.

POURED CONCRETE OR BLOCK WALL FOUNDATION

ULC LABELLED CANADIAN GYPSUM COMPANY "SHEETROCK FIRECODE C" OR "SHEETROCK SW FIRECODE C"

STRUCTURAL CAPACITY FOR WALL NOT TO EXCEED 32.4 kn/m (2217 LBS. PER LINEAR FOOT) FOR OTHER REQUIREMENTS, INCLUDING STRUCTURAL LOAD, REFER TO MANUFACTURER'S INSTRUCTIONS.

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
1/2" RESILIENT CHANNEL

INSTALL TOP PLATE AND CAP SECURED TO STUDS WITH 95 mm SPIRAL NAILS

50 mm RING NAILS @ 250 mm O/C (TYP)

5/8" TYPE C GYPSUM BD.  
5/8" TYPE C GYPSUM BD.  
1/2" RESILIENT CHANNEL

DOUBLE STUD SPLINE SECURED TO PLATE WITH 83 mm SPIRAL NAILS

NOTE: TESTED IN CONFORMANCE WITH CAN/ULC-S101-M, "FIRE ENDURANCE TESTS OF BUILDING CONSTRUCTION AND MATERIALS"



**Thermapan**  
Structural  
Insulated  
Panels

www.thermapan.com  
1-877-443-WALL (9255)

TITLE

60 MIN. PARTYWALL  
DOUBLE WALL STC RATING 50

REFERENCE

7016

SCALE

N.T.S.

DATE


SEPTEMBER 2011

REVISION

DWG. No.

4 W-PW-3

NOTE: TESTED IN CONFORMANCE WITH CAN/ULC-S101-M, "FIRE ENDURANCE TESTS OF BUILDING CONSTRUCTION AND MATERIALS"



ASSEMBLY OF RESILIENT CHANNEL (5)

THE RESILIENT CHANNELS ARE ORIENTED VERTICALLY AT 16" (400 mm) OC AND SECURED WITH 1" (25 mm) TYPE W GYPSUM BOARD SCREWS AT 16" (400 mm) OC TO THE STRUCTURAL INSULATED PANEL (SIP).

ASSEMBLY OF SONOSECUR ACOUSTIC PANEL (4)

TACK THE SONOSECUR ACOUSTIC PANEL WITH 1" (25 mm) LONG TYPE W GYPSUM BOARD SCREWS TO HOLD IN PLACE. THE SONOSECUR ACOUSTIC PANEL IS ASSEMBLED ON ONE SIDE ONLY.

ASSEMBLY OF FIRST LAYER 5/8" TYPE C GYPSUM (6)

INSTALL THE FIRST GYPSUM LAYER (6) VERTICALLY ONTO RESILIENT CHANNELS WITH 1" (25 mm) TYPE W GYPSUM SCREWS SPACED 16" (400 mm) OC.

ASSEMBLY OF SECOND LAYER 5/8" TYPE C GYPSUM (7)



THE JOINTS OF THE SECOND LAYER SHOULD BE OFFSET AND STAGGERED FROM FIRST LAYER. THE SECOND LAYER SHOULD HAVE 1.75" (44 mm) SCREWS AT 12" (304 mm) OC. THE FIRST LAYER OF GYPSUM DOES NOT HAVE TO BE TAPED. ONLY THE SECOND LAYER HAS TO BE FINISHED. JOINTS SHOULD BE COVERED WITH COMPOUND, COVERED WITH JOINT TAPE AND COVERED WITH AN ADDITIONAL TWO COATS OF JOINT COMPOUND. SCREW HEADS COVERED WITH JOINT COMPOUND.

UL GYPSUM BOARD FIRECODE "C"



www.thermapan.com  
1-877-443-WALL (9255)

|   |  |          |          |
|---|--|----------|----------|
| TITLE   |  |          |          |
| PARTYWALL ELECTRICAL DETAIL<br>(60 MIN. WALL RATED ASSEMBLY<br>(DOUBLE WALL) STC RATING 50) |  |          |          |
| REFERENCE   |  | SCALE    |          |
| 8015  |  | N.T.S.   |          |
| DATE  |  | REVISION | DWG. No. |
| SEPTEMBER 2011  |  | 4        | W-PW-4   |



NOTE: REFER TO W-1 FOR SPLINE CONNECTION DETAILS. REFER TO AIR BARRIER (AB-1 & AB-2) AND VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.

THE PANELS ARE FASTENED TO THE POST AT THE CORNERS AS SHOWN LEAVING A GAP TO BE SEALED WITH EXPANDING SPRAY FOAM.

DIMENSIONAL LUMBER INLAYS COMPLETE THE NAILING SURFACE AT THE CORNER.



www.thermapan.com  
1-877-443-WALL (9255)

TITLE  
**VERTICAL PANEL CONNECTIONS  
SPLINE & CORNER  
(TIMBERFRAME)**

PROJECT

REFERENCE

SCALE

N.T.S.

DATE


REVISION

DWG. No.


FEBRUARY 2012


5

W-TF-1




**NOTE:** REFER TO AIR BARRIER (AB-1 & AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.

|  |  |          |         |  |
|--|--|----------|---------|--|
|  <p>www.thermapan.com<br/>1-877-443-WALL (9255)</p> | TITLE  |          | PROJECT |  |
|  | <b>HORIZONTAL CONNECTIONS AT BEAMS (TIMBERFRAME)</b> |          |         |  |
|  | REFERENCE  | SCALE    |         |  |
| DATE   | REVISION   | DWG. No. |         |  |
| FEBRUARY 2012  | 2  | W-TF-2   | N.T.S.  |  |



**NOTE:** REFER TO AIR BARRIER (AB-2) & VAPOUR BARRIER (VB-1) DETAILS FOR SEALING SIP CONNECTIONS.



www.thermapan.com  
1-877-443-WALL (9255)

|   |          |          |  |
|---|----------|----------|--|
| TITLE   |          | PROJECT  |  |
| FOUNDATION DETAILS<br>DECK OPTIONS<br>(TIMBERFRAME) |          | PROJECT  |  |
|   |          | SCALE    |  |
| REFERENCE   | N.T.S.   |          |  |
| DATE  | REVISION | DWG. No. |  |
| FEBRUARY 2012                                       | 4        | W-TF-3   |  |

## APPENDIX A

### Panel Header/Lintel Load Tables

#### Allowable Axial Loads for 4.5" Panel Header/Lintel

| Panel Header Dimensions |           | Maximum Load       |                 |
|-------------------------|-----------|--------------------|-----------------|
| Depth (in)              | Span (ft) | Uniform Load (plf) | Point Load (lb) |
| 14                      | 4         | 1115               | 2200            |
|                         | 6         | 430                | 1300            |
|                         | 8         | 340                | 1020            |
| 20                      | 4         | 1290*              | 2600            |
|                         | 6         | 560                | 1680            |
|                         | 8         | 410                | 1200            |
| 26                      | 4         | 1420*              | 2800            |
|                         | 6         | 680                | 2040            |
|                         | 8         | 470                | 1360            |

\* Double jacks required

#### Allowable Axial Loads for 6.5" Panel Header/Lintel

| Panel Header Dimensions |           | Maximum Load       |                 |
|-------------------------|-----------|--------------------|-----------------|
| Depth (in)              | Span (ft) | Uniform Load (plf) | Point Load (lb) |
| 14                      | 4         | 1370               | 2700            |
|                         | 6         | 500                | 1500            |
|                         | 8         | 400                | 1200            |
| 20                      | 4         | 1510               | 3000            |
|                         | 6         | 650                | 1950            |
|                         | 8         | 475                | 1400            |
| 26                      | 4         | 1650               | 3300            |
|                         | 6         | 800                | 2400            |
|                         | 8         | 550                | 1600            |

#### Allowable Axial Loads for 8.25" Panel Header/Lintel

| Panel Header Dimensions |           | Maximum Load       |                 |
|-------------------------|-----------|--------------------|-----------------|
| Depth (in)              | Span (ft) | Uniform Load (plf) | Point Load (lb) |
| 14                      | 4         | 1640               | 3200            |
|                         | 6         | 625                | 1900            |
|                         | 8         | 500                | 1500            |
| 20                      | 4         | 1870               | 3750            |
|                         | 6         | 810                | 2400            |
|                         | 8         | 600                | 1750            |
| 26                      | 4         | 2060               | 4100            |
|                         | 6         | 1000               | 3000            |
|                         | 8         | 690                | 2000            |

*Note: Allowable (unfactored) loads are based on 1/4" maximum vertical deflection.*